



**art metal**

**F.P.H. Art Metal Sp.j.**

Ul. Jabłoniowa 124, 83-331 Łapino Kartuskie, Poland

Tel. 0048 58 681 80 78, Fax: 0048 58 681 80 64

www.art-metal.pl e-mail: biuro@art-metal.pl

## Pole ST3X - Catalogue card

### Construction:

1. Masking frame - cast iron.
2. Fastening disc - steel.
3. Steel pipe  $\varnothing 159$ .
4. Steel pipe  $\varnothing 88,9$ .
5. Steel pipe  $\varnothing 76,1$ .
6. Masking frame - cast aluminium.
7. Inspection door.
8. Grounding bolt.

### General information:

Pole	Standard height	Top diameter	Foundation	Maximum weight
ST3X	< 6500 mm	$\varnothing 76$	F100	80 kg
ST3X	7000 mm	$\varnothing 76$	F120	95 kg

The top of the pole depends on a luminary or a head.  
Maximum height of the lantern - 9,0 m.

### Pole finish:

- galvanizing of steel elements according to PN-EN ISO 1461
- wet, multilayer coating according to PN-EN ISO 8501-1
- standard colour RAL7021, RAL 9005, all other RAL palette colours as an option

### Load capacity:

- maximum wind area for a standard pole: 1,2 m<sup>2</sup>
- capacity for the wind area I (V = 22 m/s), II terrain category, according to PN - EN 40-3-1, PN - EN 40-3-3



### Pole fastening:

